

## **Century**<sup>™</sup> **Series**

SC 600 Series

### Quality speaks louder than words

Today's contact center and office professionals expect a lot from their headsets: They require outstanding sound performance for natural, conversational communication, extreme durability to withstand the toughest business environments and exceptional comfort for long hours of use.

The Century™ Series of wired headsets delivers on all points. In addition, the flexibility to connect to a variety of devices and stay mobile - plus seamless interaction and full call control with all major Unified Communications platforms and phone solutions. The Century  $\mbox{^{\rm TM}}$ Series of wired headsets covers every situation with premium quality and style.

#### **BENEFITS & FEATURES**

- Natural listening experience With Sennheiser Voice Clarity
- Perfect speech output Ultra noise-cancelling microphone
- **Outstanding sound quality** High-quality neodymium speaker
- High-quality durable design Brushed aluminum and stainless steel components
- Extreme durability Unibody headband construction for maximum strength at stress points
- Exceptional wearing comfort Large leatherette ear pads for all day comfort and powerful sound
- Personal fit Extension headband with number indications for accurate adjustment
- Easy to store and bring along With fold-flat ear cups and carry pouch

See more at www.sennheiser.com/century



The Century™ Series offers, with its 15 variants, connectivity to a variety of devices. See all headset variants and connectivity options in the table overview on page 3























### **Century**<sup>™</sup> **Series**

SC 600 Series

#### **Product Data**

Wearing Style	Headband – single and double sided variants. See table overview.		
Color	Black with silver		
Headset weight	Single sided 59 g / 2.1 oz		
	Double-sided 95 g / 3.4 oz		
Audio			
Sennheiser Voice Clarity	For a clear and natural listening experience		
Microphone	Ultra noise-cancelling microphone for optimal speech transmission		
Microphone frequency range	150 – 6,800 Hz (Wideband)		
Speaker type	High-quality neodymium magnet speaker for outstanding audio quality		
Speaker frequency response	50 - 18,000 Hz		
– multimedia	50 - 12,000 Hz (SC 638 / SC 668)		
Sound pressure	Limited by ActiveGard®:		
	Max. 103 dB via ED Max. 110 dB via ED (SC 638 / SC 668)		
	Max. 113 dB via USB		
	Max. 118 dB via 3.5 mm jack		
Made for communication &	Sound enhancement profiles adjust		
multimedia	automatically for optimal communi- cation or multimedia use*		
	cation of mutumedia use		
Hearing Protection			
ActiveGard® Technology	Protects users against acoustic injury caused by sudden sound burst on the line		

*Available	when	the	heads	et is	conne	cted	via	USB

<sup>\*\*</sup>In compliance with EU Noise at Work legislation (Directive 2003/10/EC)

over a work day

Enhanced audio protection preventing listening fatigue, average 85 dB

EU Noise at Work limiter\*/\*\*

#### Easy Call Management

In-line call control (USB)	Answer/end call, volume up/down and mute
In-line mini call control (3.5 mm jack)***	Answer/end call

#### **Long-Term Reliability**

Vectran™ reinforced cable	For extreme durability
Unibody headband construction	For maximum strength
Warranty	3 years

#### Content of delivery

What's in the box	Headset, quick guide, safety guide,
	leatherette ear pad/s, carry pouch,
	magnetic holder, cable clip mounted
	on headset,

#### **Cloud Based Asset Management**

HeadSetup™ Pro Manager	Manage, update and configure your
	Sennheiser audio devices from one
	location:

www.sennheiser.com/headsetup-pro-manager

For information about accessories and spare parts go to: vww.sennheiser.com/century

<sup>\*\*\*</sup>Available on variants: SC 635 USB & SC 665



# **Century**<sup>™</sup> **Series Overview**

SC 600 Series



Connects to		Product name /Art.no	Description	Details	EAN no. / UPC no.
Desk phone via Easy Disconnect (ED)		<b>SC 630</b> Art. no 504556	Single-sided, ED	Optimized for use with desk phones	EAN: 40 44155 08347 7 UPC: 6 15104 23704 9
		SC 660 Art. no 504557	Double-sided, ED	Easy Disconnect plug with quick release mechanism	EAN: 40 44155 08348 4 UPC: 6 15104 23708 7
Special requirements	SC 632 Art. no 504558	Single-sided, ED, low impedance		EAN: 40 44155 08349 1 UPC: 6 15104 23712 4	
	uiremer	SC 662 Art. no 504559	Double-sided, ED, low impedance	<ul> <li>Optimized for low impedance devices</li> </ul>	EAN: 40 44155 08350 7 UPC: 6 15104 23714 8
	SC 638 Art. no 506494	Single-sided, ED, narrowband		EAN: 40 44155 20496 4 UPC: 6 15104 26739 8	
	Spe	SC 668 Art. no 506495	Double-side, ED, narrowband	<ul> <li>Optimized for narrowband desk phones</li> </ul>	EAN: 40 44155 20497 1 UPC: 6 15104 26744 2
+T) TELECOIL		<b>SC 660 TC</b> Art. no 507099	Double-sided, ED, hearing aid	Optimized for all standard telecoil hearing aids	EAN: 40 44155 21456 7 UPC: 6 15104 28066 3
PC via USB	SC 630 USB CTRL Art. no 504554	Single-sided, USB, UC optimized	Optimized for UC	EAN: 40 44155 08345 3 UPC: 6 15104 23698 1	
	SC 660 USB CTRL Art. no 504555	Double-sided, USB, UC optimized	In-line call control for easy call management	EAN: 40 44155 08346 0 UPC: 6 15104 23700 1	
	SC 630 USB ML Art. no 504552	Single-sided, USB, Skype for Business Certified	Certified for Skype for Business	EAN: 40 44155 08343 9 UPC: 6 15104 23696 7	
	SC 660 USB ML Art. no 504553	Double-sided, USB, Skype for Business Certified	In-line call control for easy call management	EAN: 40 44155 08344 6 UPC: 6 15104 23697 4	
PC, smartphone and tablet via USB/3.5 mm jack	<b>SC 635 USB</b> Art. no 507254	Single-sided, USB/3.5 mm jack	Optimized for UC & Certified for Skype for Business	EAN: 40 44155 22408 5 UPC: 6 15104 30132 0	
	SC 665 USB Art. no 507257	Double-sided, USB/3.5 mm jack	Offering added mobility and flexibility	EAN: 40 44155 22411 5 UPC: 6 15104 30135 1	
Smartphone and tablet via 3.5 mm jack		<b>SC 635</b> Art. no 507253	Single-sided, 3.5 mm jack	For phones/tablets with 3.5 mm connector*	EAN: 40 44155 22407 8 UPC: 6 15104 30131 3
		SC 665 Art. no 507256	Double-sided, 3.5 mm jack	USB controller cable available as accessory	EAN: 40 44155 22410 8 UPC: 6 15104 30134 4

 $<sup>\</sup>ensuremath{^{\star}}\xspace \text{Compatible}$  with other connection types when adaptor is used.