EXPAND Vision 1M

EXPAND Vision 1M

Conference Camera for Effective Meetings

Complete your meeting space with the EXPAND Vision 1M, an easy-to-use USB camera for small and mediumsized meeting rooms. This camera fits perfectly as an integrated part of a native meeting room solution or into any bring-your-own-device meeting room.

The 4K camera is optimized to produce the best picture in any light conditions. You will look professional and easily engage with remote colleagues. Experience hassle-free calls with intelligent picture framing that automatically adjusts the view based on the number of participants.

Enjoy seamless collaboration with a solution that is certified for leading UC providers. Get the perfect picture by configuring the camera settings through EPOS Manager, your centralized device management platform. Secure privacy when needed with a single press of a button.

See more at eposaudio.com/expand-vision-1m



Key Benefits & Features

Designed for any meeting space

Easily bring video into any meeting space. Fits perfectly as part of a native meeting room solution or a BYOD room setup.

Be seen at your best

Look professional on any video call with a 4K camera and intelligent picture framing that captures all inroom participants.

Trusted stamp of approval

Certified for leading UC solutions and works in any Android or Windows environment.

Sleek, elegant design

The minimalist, smooth design and a camera without moving parts minimize distractions, letting everyone focus on the meeting.

Instant privacy

For the moment where you need complete privacy, simply press the button at the top to activate the integrated shutter.



EP3S

EXPAND Vision 1M

Product data

General

Color	Black	
Weight	500 g / 17.637 oz	
Dimensions (W x H x L)	194 x 34 x 42 mm / 7,6 x 1,3 x 1,7 in	
Warranty	2 years	
Technical		
UC application	Certified and optimized for leading UC providers	
Supply voltage	5 V	
Power consumption	3,75 W	
Operating temperature (Max)	40 °C / 104 ° F	
Operating temperature (Min)	0 °C / 32 °F	
Operating humidity (Max)	90%	
Storage temperature (Min)	-40 C / -40 F	
Storage temperature (Max)	60 °C / 140 °F	

Camera	4K wide-angle
Lens type	4G2P
Video resolution	Up to 2160p @ 30fps
Zoom	8x digital
Pan-tilt-zoom (PTZ)	ePTZ
Field of view (FOV)	95° (Horizontal) / 62° (Vertical) / 103° (Diagonal)
Video standards	MJPEG, H264
Depth of Field	Manual. With the range of 1 - 6 m in focus / 3,3 - 19,8 ft
Mounting Options	Integrated clip with 1/4" thread for tripod mounting
Automatic light correction	Optimized for best picture quality in various light conditions
LED light	White when in use. Dime when in standby mode
Device Administration	
Remote management	EPOS Manager or UC provider solutions
Firmware updates	Automatic
EPOS Connect	Download EPOS Connect to control zoom and light, adjust colors etc.
Privacy/Security	
Lens cover	Integrated motorized privacy shutter

ı y

What's in the box

EPOS EXPAND Vision 1M USB camera, 3 m USB-C to USB-A 3.0 video cable and Safety guide

EXPAND Vision 1M

Additional Benefits & Features

Intuitive wall mount

The included wall mount lets you easily install the camera and adjust its angle for optimal positioning.

Streamlined cable management

Angled plug guides the USB-C cable away to avoid interference with other devices

Kensington lock option

Provides peace of mind that the camera will remain in its designated place

Warranty and support

Protect your investment with a two-year warranty and access to EPOS support.

Helpful LEDs

Two LED lights on the sides of the camera indicate when a call is in progress.

Product overview

Connects to	Product	Description	EAN / UPC code
Screen/monitor	EXPAND Vision 1M	USB Camera for small and	EAN: 57 14708 01001 2
via HDMI	Art. no. 1001197	medium-sized meeting rooms	UPC: 8 40064 41001 4
			
	EXPAND Vision 1M	Wall bracket for EXPAND Vision 1M	EAN: 57 14708 01038 8
	- WM 01 Art. no. 1001231	(included)	UPC: 8 40064 41038 0
	EXPAND Vision 1M	3 m USB-C to USB-A cable for	EAN: 57 14708 01048 7
	USB-C cable Art. no. 1001241	EXPAND Vision 1M (included)	UPC: 8 40064 41048 9

